



PRODUCT CODES

- OC900EP-6
- OC900ET-6
- OC900EP-81
- OC900ET-81
- OC900CP-6
- OC900CT-6
- OC900DP-6
- OC900DT-6
- OC9006P-6
- OC9006P-144
- OC9006T-6
- OC9006T-144

Access Point Medical™ adds distribution of Catalina Cylinders to its product line

Product Overview Catalina medical cylinders are available in two valve types: post and toggle. Access Point Medical distributes four different cylinder sizes: E-cylinder, D-cylinder, M6 and M9. All store oxygen in lightweight aluminum cylinders produced from a high-strength aluminum alloy 6061-T6. The standard finish is brushed body with a green shoulder and clear coat of heat sensitive powder paint.

Regulation All seamless aluminum alloy compressed gas cylinders are manufactured in accordance with U.S. Department of Transportation (DOT) 3AL and Transport Canada (TC) 3ALM requirements. Every cylinder is inspected and tested by a DOT and TC authorized independent inspection agency.

- Features**
- High-performance, light weight design
 - Highly portable and easy to maneuver
 - Exceptional strength and durability
 - Non-magnetic
 - Shipped empty

Product Code	Cylinder Size Valve Type	Case Qty.	Service	Diameter	Length	Empty Weight	Oxygen	Water	Thread Size
OC900EP-6	E, post valve	6	2015 psi	4.38"	24.9"	7.4 lbs	680 liters	4.6 liters	.750-16UNF-2B
OC900ET-6	E, toggle valve	6	2015 psi	4.38"	24.9"	7.4 lbs	680 liters	4.6 liters	.750-16UNF-2B
OC900EP-81	E, post valve	81	2015 psi	4.38"	24.9"	7.4 lbs	680 liters	4.6 liters	.750-16UNF-2B
OC900ET-81	E, toggle valve	81	2015 psi	4.38"	24.9"	7.4 lbs	680 liters	4.6 liters	.750-16UNF-2B
OC900DP-6	D, post valve	6	2015 psi	4.38"	16.5"	5.1 lbs	425 liters	2.9 liters	.750-16UNF-2B
OC900DT-6	D, toggle valve	6	2015 psi	4.38"	16.5"	5.1 lbs	425 liters	2.9 liters	.750-16UNF-2B
OC900CP-6	M9, post valve	6	2015 psi	4.38"	10.7"	3.6 lbs	255 liters	1.7 liters	.750-16UNF-2B
OC900CT-6	M9, toggle	6	2015 psi	4.38"	10.7"	3.6 lbs	255 liters	1.7 liters	.750-16UNF-2B
OC9006P-6	M6, post valve	6	2216 psi	3.21"	11.6"	2.2 lbs	170 liters	1.0 liters	.750-16UNF-2B
OC9006T-6	M6, toggle valve	6	2216 psi	3.21"	11.6"	2.2 lbs	170 liters	1.0 liters	.750-16UNF-2B
OC9006P-144	M6, post valve	144	2216 psi	3.21"	11.6"	2.2 lbs	170 liters	1.0 liters	.750-16UNF-2B
OC9006T-144	M6, toggle valve	144	2216 psi	3.21"	11.6"	2.2 lbs	170 liters	1.0 liters	.750-16UNF-2B