

PRODUCT CODE

AXS34

AXS34L



AXS 34 Rear Wheel Drive Power Scooter, easy on-and-off access, shown here with light

Product Overview The AXS 34 Scooter offers maneuverability, comfort and speed with a three wheeled, rear-drive transaxle design. This exciting scooter is designed for indoor and outdoor maneuverability with speeds up to 5.4 mph giving the user more travel options. The premium seat design offers exceptional comfort and adjustability to meet users' seating needs.

- Features**
- Rear-drive design provides top performance both indoors and outdoors
 - Premium padded seating offers comfort and adjustability for all users and swivels 90° in either direction
 - Seat adjusts from 22" to 26" heights (ground to seat top)
 - Easy take-apart design offers users' maximum travel flexibility
 - Maximum capacity of 300 lbs.
 - Long lasting durable solid-steel frame
 - Max Climbing Angle: 15°, 25% grade
 - Turning Radius: 37.75"
 - Speeds up to 5.4 mph and battery range up to 25 miles

Warranty 1 year limited warranty

Accessories U1 batteries are sold separately.

Standard Configuration Premium seats, armrests, battery charger, pneumatic tires

Optional Configuration Standard configuration plus lights

DRIVE TRAIN	Rear-Wheel Drive
RECOMMENDED TERRAIN	Indoor/Outdoor
SPEED DIAL CONTROL	Yes
SPEED CONTROL TYPE	Variable
SPEED	Forward: 5.4 mph (8.7 kmph) Reverse: 2.5 mph (4 kmph)
GROUND CLEARANCE	2" - 3.5" (63.5 - 88.9 mm)
OVERALL WIDTH	24.5" (622.3 mm)
OVERALL LENGTH	47" (119.38 cm)
WHEELBASE	Length: 34" (864 mm) Width: 24.5" (620 mm)
CURB CLIMBING HEIGHT	3" (76 mm)
MAXIMUM WEIGHT CAPACITY	300 lbs. (136 kg)
MAXIMUM CLIMBING ANGLE	15° Slope 25% Grade
TURNING RADIUS	37.75" (959 mm)
BRAKE TYPE	Spring Set Manual Release
OVERALL WEIGHT WITH BATTERY	194 lbs. (97 kgs)
BATTERIES	Two U-1-31 amp/hour
RANGE	Up to 25 Mi. (40 km)
CONTROLLER	70 amp PPMC
TIRES	Pneumatic, front 9" x 3.5" (230 x 90 mm) Pneumatic, rear 10" x 3" (250 x 80 mm)
COLOR	Candy Apple Red
TILLER	Folding, Angle-adjustable without tools
LOCATION OF CONTROLS	
Power (on/off)	Top of tiller
Accelerator	Thumb
Speed Dial Control	Top of tiller
Charger Connection	Top of tiller
Battery Voltage Indicator	Top of tiller
Key Type	Microphone jack style key
POWER TRAIN	Transaxle
Drive Ratio	22.2:1 internal in transaxle
Motor Specification	2-pole; .75 hp (peak)
SEATING	Premium Seat
Seat Rotation	(+/-) 90°
Adjustable	1" increments
Seat height from ground	22" – 26"
OTHER FEATURES	Accessible Circuit Breaker 90° Swivel Seat and Adjustable Armrests